

1 SECTION 1: Identification of the substance/mixture and of the company/undertaking:

1.1 Product identification:

IF Truck Clean - article numbers A00365, A00366 - A00367

1.2 Relevant identified uses of the substance or mixture and uses advised against:

/

Use concentrations: /

1.3 Details regarding the provider of the safety data sheet:

Indufarm NV

Leon Bekaertstraat 5

8770 Ingelmunster (Belgium)

Tel: +32-51-624245

Email: contact@indufarm.com — Website: <http://www.indufarm.com>

1.4 Emergency telephone number:

+32 70 245 245

SECTION 2: Hazards identification:

2.1 Classification of the substance or mixture:

Classification of the substance or mixture according to CLP, Regulation (EC) 1272/2008:

H314 Skin Corr. 1A

2.2 Label elements:

Icons:



Signal word:

Danger

Hazard Statements:

H314 Skin Corr. 1A: Causes severe burns and eye damage.

Safety recommendations:

P280: Wear protective gloves, protective clothing, face protection. eye protection,

P301+P330+P331: IF SWALLOWED: Rinse mouth. DO NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): remove contaminated clothing immediately. Rinse skin with water/ shower.

P304+P340: IF INHALED: Remove the person to fresh air and keep them breathing easily.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for one day amount of minutes; remove contact lenses, if possible; keep rinsing.

P363: Wash contaminated clothing before reuse.

Contains:

no

2.3 Other hazards:

no

3 SECTION 3: Composition/information on ingredients:

2-butoxyethanol	γ 4% CAS no.:	111-76-2
	EINECS:	203-905-0
	REACH Registration No.:	01-2119475108-36
	CLP Classification:	H302 Acute toxic. 4 H312 Acute toxic. 4 H315 Skin Irrit. 2 H319 Eye Irrit. 2 H332 Acute toxic. 4
Sodium lauryl ether sulfate	γ 3% CAS no.:	68891-38-3
	EINECS:	500-234-8
	REACH Registration No.:	01-2119488639-16
	CLP Classification:	H315 Skin Irrit. 2 H318 Eye Dam. 1 H412 Aquatic Chronic 3
Ethylenediaminetetraacetic acid, 4Na	γ 3% CAS no.:	64-02-8
	EINECS:	200-573-9
	REACH Registration No.:	01-2119486762-27
	CLP Classification:	H302 Acute toxic. 4 H318 Eye Dam. 1 H332 Acute toxic. 4
Sodium hydroxide	γ 2% CAS No.:	1310-73-2
	EINECS:	215-185-5
	REACH Registration No.:	01-2119457892-27
	CLP Classification:	H290 Met. Corr. 1 H314 Skin Corr. 1A

For the full text of the H statements mentioned in this section, see section 16.

4 SECTION 4: First aid measures:

4.1 Description of first aid measures:

Always seek medical advice as soon as possible in case of serious or persistent disorders.

Skin contact:	Remove contaminated clothing, rinse skin with plenty of water and immediately hospital transport.
Eye contact:	First rinse with water for a long time (remove contact lenses if easy possible), then take it to a doctor.
Ingestion:	Rinse mouth, DO NOT induce vomiting and go to hospital immediately transport.
Inhalation:	Sit upright, get fresh air, rest and transport to hospital.

4.2 Most important acute and delayed symptoms and effects:

Skin contact:	caustic, redness, pain, severe burns
Eye contact:	caustic, redness, poor vision, pain
Ingestion:	biting, shortness of breath, vomiting, blisters on lips and tongue, burning pain in mouth and throat, esophagus and stomach
Inhalation:	headache, dizziness, nausea, drowsiness, unconsciousness

4.3 Indication of any immediate medical attention and special treatment needed:

no

5 SECTION 5: Firefighting measures:

5.1 Extinguishing media:

water spray, powder, foam, CO2

5.2 Special hazards arising from the substance or mixture:

no

5.3 Advice for firefighters:

Extinguishing media to avoid: **no**

6 SECTION 6: Accidental release measures:

6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances. Avoid exposure to fumes, smoke, dust and vapor breathe by staying upwind. Any soiled garment and protective equipment soiled after use remove it and dispose of it safely.

6.2 Environmental precautions:

Do not allow to enter sewers or public waters.

6.3 Methods and material for containment and cleaning up:

Carefully collect spilled product and store in suitable containers. If necessary, allow it to be absorbed by absorbent material material.

6.4 Reference to other sections:

For further information see sections 8 & 13.

7 SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Handle with care to avoid leaks.

7.2 Conditions for safe storage, including incompatibilities:

Store in tightly closed packaging in a closed, frost-free, ventilated area.

7.3 Specific end use:

/

8 SECTION 8: Exposure controls/personal protection:

8.1 Control parameters:

Below is a list of hazardous components listed in section 3 for which the TLV values are known

2-butoxyethanol 98 mg/m³, Sodium hydroxide 2 mg/m³

8.2 Exposure controls:

Inhalation protection:	Use with adequate exhaust ventilation. Where breathing risks occur, use an air purifying face mask if necessary. As protection against these stressful levels, use type ABEK.	
Skin protection:	Handle with nitrile gloves (EN 374). Minimum breakthrough time of > 480 minutes, thickness 0.35mm. Check gloves carefully before use. Remove gloves neatly without touching the outside with your bare hands hand. The suitability for a specific workplace must be discussed with the manufacturer of protective gloves. Wash and dry hands.	
Eye protection:	Keep eye washes with clean water within reach. Close fitting safety goggles. Wear a face shield and protective suit for exceptional processing problems.	
Other protection: the	Impermeable clothing, The type of protective equipment depends on concentration and quantity of hazardous substances at the workplace.	

9 SECTION 9: Physical and chemical properties:

9.1 Information on basic physical and chemical properties:

Melting point/melting range:	0°C
Boiling point/boiling range:	100°C — 173°C
pH:	13.5
pH 1% diluted in water:	/
Vapor pressure at 20°C:	2 332 Pa
Vapor density:	Technically impossible

Relative density at 20°C:	1.0744 kg/l
Appearance at 20°C:	liquid
Flash point:	/
Flammability (solid, gas):	Technically impossible
Auto-ignition temperature:	230°C
Upper flammability or explosion limit (Vol %):	10.600%
Lower flammability or explosive limit (Vol %):	1,130%
Explosion properties:	Technically impossible
Oxidizing properties:	Technically impossible
Decomposition temperature:	/
Water solubility:	completely soluble
Partition coefficient n-octanol/water:	Technically impossible
Odor:	characteristic
Odor threshold:	Technically impossible
Dynamic viscosity at 20°C:	1 mPa.s
Kinematic viscosity at 40°C:	1 mm ² /s
Evaporation rate (n-BuAc = 1):	0.300

9.2 Other information:

Volatile Organic Compound (VOC):	3.35%
Volatile Organic Compound (VOC):	36,000 g/l
Flammability test:	/

10 SECTION 10: Stability and reactivity:

10.1 Reactivity:

Stable under normal conditions.

10.2 Chemical stability:

Avoid extremely high or low temperatures.

10.3 Possibility of hazardous reactions:

no

10.4 Conditions to avoid:

Protect from sunlight. Do not expose to temperatures above 50°C

10.5 Incompatible materials:

no

10.6 Hazardous decomposition products:

Does not decompose under normal use

11 SECTION 11: Toxicological information:

11.1 Information on toxicological effects:

H314 Skin Corr. 1A: Causes severe burns and eye damage.

Calculated acute toxicity, ATE oral: /

Calculated acute toxicity, ATE dermal: /

2-butoxyethanol	LD50, Oral, Rat:	1 200 mg/kg
	LD50, Dermal, Rabbit:	1 100 mg/kg
	LC50, Inhalation, 4h:	11 mg/l
Sodium lauryl ether sulfate	LD50, Oral, Rat:	ÿ 5,000 mg/kg
	LD50, Dermal, Rabbit:	ÿ 5,000 mg/kg
	LC50, Inhalation, 4h:	ÿ 50 mg/l
Ethylenediaminetetraacetic acid, 4Na	LD50, Oral, Rat:	500 mg/kg
	LD50, Dermal, Rabbit:	ÿ 5,000 mg/kg
	LC50, Inhalation, 4h:	10 mg/l
Sodium hydroxide	LD50, Oral, Rat:	ÿ 5,000 mg/kg
	LD50, Dermal, Rabbit:	ÿ 5,000 mg/kg
	LC50, Inhalation, 4h:	ÿ 50 mg/l

12 SECTION 12: Ecological information:

12.1 Toxicity:

2-butoxyethanol	LC50 (Pisces):	1474 mg/L (Oncorhynchus mykiss)(96h)
	EC50 (Daphnia):	1550 mg/L (48h)
	NOEC (Daphnia):	>100 mg/L (72h)
	EC50 (Algae):	911 mg/L (72h)
	NOEC (Algae):	>280 mg/L (72h)
Sodium lauryl ether sulfate	LC50 (Pisces):	7.1 mg/L (96h)
	EC50 (Daphnia):	7.2 mg/L
	EC50 (Algae):	27mg/L
	NOEC (Algae):	0.93 mg/L
	EC50 (Bacteria):	7.5 mg/L
Ethylenediaminetetraacetic acid, 4Na	LC50 (Pisces):	121 mg/L (96h)
	EC50 (Daphnia):	625 mg/L (24h)
Sodium hydroxide	LC50 (Pisces):	35 - 189 mg/L (96h)
	EC50 (Daphnia):	33 - 450 mg/L (48h)

12.2 Persistence and degradability:

The surfactants in this preparation meet the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents.

12.3 Bioaccumulative potential:

no additional data available

12.4 Mobility in the soil:

WGK class (AwSV): 1
Water solubility: completely soluble

12.5 Results of PBT and vPvB assessment:

no additional data available

12.6 Other harmful effects:

no additional data available

13 SECTION 13: Disposal considerations:

13.1 Waste treatment methods:

The product may be discharged at the indicated use concentrations, if necessary, after neutralization to pH 7. Any restrictive measures taken by the local authority must always be observed.

14 SECTION 14: Transport information:

14.1 UN number:

1719

14.2 UN proper shipping name:

UN 1719 Corrosive alkaline liquid, nos (mixture with sodium hydroxide), 8, III, (E)

14.3 Transport hazard class(es):

Class(es) : 8
Identification number of the
danger: 80

14.4 Packing group:

III

14.5 Environmental hazards:

not environmentally hazardous

14.6 Special precautions for the user:

Hazard properties: Risk of burns. Risk to the aquatic environment and wastewater disposal systems.

Additional instructions: Prevent leakage of substances into the aquatic environment or into the sewage system end up.



15 SECTION 15: Regulations:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

WGK class (AwSV):	1
Volatile Organic Compound (VOC):	3.351%
Volatile Organic Compound (VOC):	36,000 g/l
Composition according Regulation (EC) 648/2004:	Anionic surfactants < 5%, EDTA and its salts < 5%

15.2 Chemical Safety Assessment:

No data available

16 SECTION 16: Other information:

Glossary of abbreviations:

ADR:	Accord européen relatif au transport international des marchandises Dangereuses par Route
ATE:	Acute Toxicity Estimate
BCF:	Bioconcentration factor
CAS:	Chemical Abstracts Service
CLP:	Classification, Labeling and Packaging of chemicals
EINECS:	European INventory of Existing Commercial chemical Substances
LC50:	median Lethal Concentration for 50% of subjects
LD50:	median Lethal Dose for 50% of subjects
No.:	number
PTB:	persistent, toxic, bioaccumulative
TLV:	Threshold Limit Value
WGK:	Water Hazard Class
WGK 1:	little hazardous to water
WGK 2:	dangerous for water
WGK 3:	very dangerous for water
vPvB:	very persistent and highly bioaccumulative substances

Explanatory list of the H-phrases used in this safety data sheet:

H290 Met. Corr. 1: May be corrosive to metals. H302 Acute toxic. 4: Harmful if swallowed.
H312 Acute toxic. 4: Harmful in contact with skin. H314 Skin Corr. 1A: Causes severe burns and eye injury. H314 Skin Corr. 1A: Causes severe burns and eye damage. H315 Skin Irrit. 2: Causes skin irritation.
H318 Eye Dam. 1: Causes serious eye damage. H319 Eye Irrit. 2: Causes serious eye irritation. H332 Acute toxic. 4: Harmful by inhalation. H412 Aquatic Chronic 3: long lasting effects. Harmful to aquatic organisms, with

CLP Calculation Method:

Based on test data for Corrosivity, based on calculation method for other hazard classes

Reason for revision, changes in the following sections:

Technically impossible

MSDS reference number:

ECM-111194.00

This safety information sheet has been drawn up in accordance with Annex II/A of Regulation (EU) 2015/830. Classification has been calculated in accordance with European Regulation 1272/2008 with their respective amendments. She is with the greatest possible prepared with care. However, we cannot accept liability for damage of any kind caused by the use of this data or the product in question. Before using this preparation for a experiment or a new application, the user must carry out a material suitability and safety study himself.