

COOL BOX

NT-30 and NT-15

- Peltier cell thermoelectric heating and cooling.
- Digital regulator with resolution 0.1°C
- Built-in neutral zone that reduces the power consumption of the box and extends its useful life.
- A+ rating that reduces energy consumption by 25%.
- Nominal power: 75 / 65-80 W.
- Voltage: 220 VAC/12-24 DC.
- Frequency: 50/60 Hz.
- Consumption: 4 A.
- Nominal volume: NT-30 34 L - NT-15: 14L.
- Optimal Semenbag doses: NT-30 120 - NT-15: 60.

NT-110

- Heating and cooling by gas compression circuit.
- Digital regulator with resolution 0.1°C
- Built-in neutral zone that reduces the power consumption of the box and extends its useful life.
- CFC-free cooling element.
- A+ rating that reduces energy consumption by 25%.
- Nominal power: 220/75 W.
- Voltage: 100-240 VAC/12-24 DC.
- Frequency: 50/60 Hz.
- Consumption: 10 A.
- Nominal volume: 95 Litres.
- Optimal Semenbag doses: 435.



CE

10 Kg
54 x 36 x 46 cm

11,2 Kg
58 x 40 x 49 cm

CE

7 Kg
44 x 33 x 29 cm

7,4 Kg
48 x 32 x 36 cm



CE

33 Kg
96 x 53 x 47 cm

38 Kg
100 x 58 x 53 cm



DATALOGGER USB

Temperature reading and storage.

DATAPAD

For direct reading and configuration.