VRH-3D VALVE



Constant level valve for gestation, farrowing, weaning and fattening

The **VRH-3D** maintains a constant water level in any container where it is applied, working only with the pressure of the water that flows through it.

It is a more versatile and economic upgrade of the successful VR-H, which when launched in 2001 revolutionized the way that water is dispensed in pig farming by simplifying and increasing consumption and reducing waste.





FEATURES

- 1/2 "water inlet with adjustable rear tap.
- · Vacuum membrane suction sealing system.
- · Water stops on reaching level of metal downpipe.
- · Closure system at water inlet.
- · Manual system for opening body.
- · Adjustable water line connector.
- · Lower minimum operational pressure.

ADVANTAGES

- Simple and reliable operation at a wide range of pressures.
- · Easy to set up even in existing systems.
- · High water flow rate.
- · Works with both large and small pans.

TECHNICAL DETAILS

VRH-3D VALVES						
Number of animals 1-20						
Pressure, bar	min.	max.				
riessuie, vai	0,5	2,5				
Fl 1/	min.	max.				
Flow, I/min.	1,8	3,6 - 4,2				

FLYER	WEB	VIDEO	INSTRUCTIONS	MANUAL
YES	YES	YES	19300009	YES

PACKAGING INFORMATION

CODE	PRODUCT	UNIT PURCHAS				wxtxH Innlimilimi	(Kg	m^3	
19301000	VRH-3D VALVE	5	U.	50	750	120 x 100 x 122	150,7	1,46	

VRH-3D VALVE



PRODUCT ACCESSORIES

U0000346	Ø 1/2" SS VRH-3 PIPE 1180 mm
U0000489	TUBO VRH-3 INOX Ø 1/2" A 1500 mm

Downpipe of the water.

FLYER	WEB	VIDEO	INSTRUCTIONS	MANUAL
NO	N0	N0	NO	NO

10300020 I	DEOBTURATOR
------------	-------------

It is installed inside the tube to prevent it from blocking with feed.

FLYER	WEB	VIDEO	INSTRUCTIONS	MANUAL
NO	YES	NO	NO	NO



PACKAGING ACCESSORIES INFORMATION

CODE	PRODUCT	MULTIPLI Unit Purchas				wxtxH Imilmilmilmil	@ Kg	m^3
U0000346	Ø 1/2" SS VRH-3 PIPE 1180 mm	5	U.	5	360	120 x 100 x 34	182,0	0,74
U0000489	TUBO VRH-3 INOX Ø 1/2" A 1500 mm	5	U.	5	360	120 x 100 x 34	182,0	0,74
10300020	DEOBTURATOR	1	U.	-	-	-	-	-